

CATALOGUE



SECURITY WORLD TECHNOLOGY LTD.

Security & Safety Solution Provider

Kenya | Uganda | Tanzania | Rwanda

www.securityworldtech.com

About Us

What started as a Small Business Enterprise in 1998 has grown tremendously over the years. With the name change and re-branding in the year 2005, Security World Technology Limited became the leading importer, distributor and provider of reliable, cost effective solutions in the region.

Security World Technology Limited stocks a wide range of world class products and security solutions backed by unrivalled technical and sales support, product training and value added services to ease your business concerns.

Security World Technology Limited has gone from strength to strength in building a dynamic distribution network covering Kenya (Head Office), Uganda, Tanzania and Rwanda that supplies dealerships and service providers across the entire East and Central Africa Region.

Mission

Endeavor and dedicate to deliver advanced security and safety technology solutions that exceed our customer's expectation and meet industry standards.

Vision

To be preferred security and safety technology solutions provider and distributor in our market

Core Business...

We specialize in sourcing, stocking and supplying of security equipment and solutions. SWTL offers of the popular "one stop shop" concept, providing an extensive inventory range with the latest products and technology.

We are single source supplier of security products and offer 'Total Security Solutions' backed by dedicated technical and sales support who are always in hand to quote and assist with design to enable you provide scalable security solutions that meets and exceed your customer's needs.

Customer Care...

We are passionate about our customers. Our experienced professional staff are at hand to advise on the latest products, with a diverse range of cutting edge security solutions designed to suit environments ranging from retail warehousing, plants to up market property developments.

Our advanced product range effectively addresses customers' needs of flexibility, reliability and competitive pricing within the security market.

We pride ourselves as the only organization in the region with the strategy to educate and train installers, technical and security consultants on current trends with the sole aim of improving industry standards.'

Visit Security World Technology Limited
www.securityworldtech.com

For more information on our full range of products and services or contact your nearest branch to discuss how Security World can add value to your business

HIKVISION



Texecom
Designed to Perform

SHERLO TRONICS

ZKSoftware
Advanced Biometric and RFID Solutions

ROSSLARE
SECURITY PRODUCTS

RISCO

KOCOM

orientx
FIRE EXTINGUISHER

GARRETT
METAL DETECTORS

NEMTEK
Electric Fencing Products

ELMDENE
Protecting People & Property

gateway

CS3

EASTIMAGE

RDC

KORLTA

BlueCard



DS-2CD2745FWD-IZS
4MP IR Vari-focal Dome Network Camera
 : 21/2.5" Progressive Scan CMOS
 : 2688 x 1520@30fps
 : 2.8 to 12 mm motorized vari focal lens
 : powered by Dark fighter
 : H.265, H.265+, H.264+, H.264
 : IR range: up to 30m



DS-2CE16D0T-IT1/IT3/IT5:
HD 1080P EXIR Bullet Camera
 : 2 MP, 1920 x 1080 resolution
 : 2.8 mm, 3.6 mm, 6mm fixed lens/2.8 mm,
 : 3.6 mm, 6 mm, 8 mm, 12 mm fixed
 : lens/3.6 mm,
 : 6 mm, 8 mm, 12 mm fixed lens
 : Smart IR, up to 30/40/80 m IR distance



DS-2CD2045FWD-I
1/2.5" Progressive Scan CMOS
 : 2688 x 1520 @30 fps
 : 2.8, 4, 6, 8, 12 mm fixed lens
 : H.265+, H.265, H.264+, H.264
 : Powered by Dark fighter
 : IR range: up to 30 m



DS-2DF7274-A
1.3MP Network Speed Dome
 : 20X Optical Zoom (4.3-86.0mm)
 : True Day/night, 3D DNR
 : 25fps(p)/30fps(N) at 1280x960 resolution
 : H.264, Dual streaming, privacy Mask
 : pan manual speed :0.10 -1600/s
 : Tilt Manual Speed :0.10 -1200/s
 : 120m IR Distance ,IP66 Weatherproof



DS-2CD2145FWD-IS)
4 mp dome camera
 : 1/2.5" Progressive Scan CMOS
 : 2560 x 1440 @30 fps
 : 2.8, 4, 6, 8, 12 mm fixed lens
 : H.265+, H.265, H.264+, H.264



2CD2646G2-IZS Acusense
4MP Varifocal Bullet Network Camera
 : High quality imaging with 4 MP resolution
 : Excellent low-light performance with powered-by-Dark Fighter technology
 : Motorized varifocal lens for easy installation and monitoring
 : Efficient H.265+ compression technology
 : Audio and alarm interface available
 : Water and dust resistant (IP66) and vandal-resistant



4 MP AcuSense Fixed Bullet Network Camera
 : High quality imaging with 4 MP resolution
 : Excellent low-light performance with powered-by-: Dark Fighter technology
 : Efficient H.265+ compression technology
 : Built-in microphone for real-time auto security(-U)



DS-9616/32/64NI-18:
Embedded 4K NVR
 : Third-party cameras supported
 : Up to 12 Megapixels resolution recording
 : Support 2-ch HDMI, 2-ch VGA, HMDII at up to 4K(3840x2160) resolution
 : Up to 64 IP cameras can be connected with 320M
 : Up to 8 SATA interfaces



DS-7716/32 NI-ST(SP)
Embedded 1.5U PoE NVR
 : 40/80Mbps Bit Rate Input Max (up to 16/32ch IP video)
 : Third-party network camera's supported
 : Up to 5 Megapixels resolution recording
 : HDMI and VGA output at up to 1920 *1080P resolution
 : 4 SATA,3 USB 2.0



7200 turbo HD pro-series DVR
 : 4-ch 1080p 1U H.265 DVR
 : 4 channels and 1 HDD 1U DVR
 : Efficient H.265 pro+ compression technology
 : Encoding ability up to 1080p @ 15 fps
 : 5 signals input adaptively (HDTVI/AHD/CVI/ CVBS/IP)
 : Up to 6 network cameras can be connected

ACCESSORIES



: Rj 45



: CAMERA WALL BRACKET



: DS-3E0109P-E/M(B)
 100M POE



: BNC CONNECTOR SCREW TYPE



: CAT 6 CABLE



1.0 TB



2.0 TB



4.0 TB



8.0 TB

HARD DRIVES

INTRUDER



LIGHTYS PLUS

- : intruder
- : LightSYS plus
- : Up To 512 zones in one panel
- : Integrated Wi-Fi and IP Modules for fast & stable communication
- : Compatible with RISCO's indoor and outdoor wireless camera detectors for visual verification
- : Unique protective cover - Securing the control panel for increased robustness
- : C-Type-USB Input - Conveniently use a standard cable for fast upgrade & setup
- : Grade 2 and Grade 3



LIGHTSYS PANEL

- : Product features: Wired, wireless or RISCO Bus detectors
- : Wireless receiver can be installed inside or outside the main enclosure
- : Selectable EOL zone resistance and remote zone resistance measurement
- : Adaptive menu tree displays only the relevant options according to hardware installed and authorized level
- : Easy firmware upgrade with ash memory



VERITAS R8

- : Best selling control panel with remote keypad.
- : Features 8 fully programmable zones and Accepts up to 6 backlit remote keypads.



PROSYS PANEL

- : Auto-Intall technology assures simple installation
- : Bus test for pinpointing faulty wiring
- : Triple EOL termination for Grade 3: Allows alarm, tamper and mask on each single zone
- : 4 groups per partion - enabled partial arming of a group of zones within a partion
- : High security features such as double password, keypad disable during scheduled arm and 2 separates buses



ACCESSORIES



OUTDOOR DETECTOR

- : Reliable PIR detection for indoor and outdoor areas
- : Two detection areas for superior stability
- : Adjustable angle
- : Two microwave and PIR Channels



Wireless Piccolo PIR / Pet PIR

- : Adjustable range of up to 10m
- : Intelligent Digital Signal Processing
- : True Temperature Compensation
- : Easy battery replacement by the end user



WIRELESS KEYFOB

- : Rolling code technology or zone assignment
- : Pocket size for keyring or pendant mounting
- : Low battery and transmission LED indication
- : Includes Lithium battery



WIRED BEYOND

- : Coverage: 12m, 90 degrees
- : Installation Height: Typical 2.2m
- : PIR: 2 dual element sensors, 2 Separate lenses
- : Anti-Mask detracton method: Active infrared
- : Pet immunity: Animals up to 35cm head height
- : Dimensions (HxWxD): 167x88x106mm
- : Direct sunlight immunity



PREMIER ODYSSEY IE

- : 109 db Single Piezo Sounder
- : IP44 Sealed Electronics Module
- : Lid and Wall Tamper
- : Advanced Microprocessor Technology
- : Patented Engineer Hold-o Mode



EXODUS OH

- : Optical and heat multisensor.
- : Heat enhancement ensures high sensitivity to fast burning res whilst optical chamber provides exceptional false alarm immunity



EXODUS RR

- : Rate of Rise heat detector.
- : Suitable for use where smoke or dust is prevalent, with fastest heat detection performance.



PREMIER IMPAQ E

- : Detection Type: Vibration
- : Adjustable Sensitivity
- : Detection/Disable/Comfort LED
- : Microprocessor Technology
- : Digital Signal Processing

FIRE DETECTION AND ACCESSORIES



FP 14 Zone Conventional Fire Panel.

- : Two conventional sounder circuits
- : Built in 24V power supply and battery charger
- : Separate indicators for open and short circuits fault, sounder fault and battery or power supply fault
- : Non-latching 'class change' sounder input, latching fire and non-latching fault outputs (available via optional expansion loom)
- : Fault buzzer mute facility



XFP Zone Single/Two LOOP Addressable Fire Alarm Panel

- : The ability to interconnect up to eight XFP main panels (any variant) onto a two wire RS485 network. Alternatively, up to eight XFP repeaters can be connected to a non networked XFP main panel.
- : Two programmable inputs.
- : A phase evacuation and delays to outputs facility (to EN54-2 Clause 7.11).
- : Powerful short circuit protected loop drivers, capable of supporting up to 40 loops powered 10mA sounders per loop.
- : An integral EN54 switch mode PSU rated @ 185-260V a.c. 50/60Hz (3A on 32 zone panel, 1.4A on 16 zone panel).



XFP Zone Single/Two LOOP Addressable Fire Alarm Panel

- : Certified to EN54-2/4 and EN12094-1 by the Loss Prevention certification Board (LPCB)
- : Functions as a standard 3 zone re panel with additional circuitry for controlling the release of re-suppressing gas.
- : Any combination of activated zones can be programmed to automatically start the panel's extinguishant release sequence.
- : Manual release button and two key switches.
- : 3 conventional sounder circuits (two x 1st stage, one x 2nd stage).
- : Wide range of monitored inputs and auxiliary outputs.
- : Abort and hold inputs.
- : Time-stamped event log.
- : RS485 connections for up to 8 flush or surface remote status units with their own LCDs, manual release and mode switches. Single gang economy status units also available.
- : Ideal for use in computer rooms, telecommunication centers, archive storage areas, museums, etc.
- : System line terminator included.



Smoke Detector

- : The xp95 Optical smoke detector works using the light scatter principle and is ideal for applications where slow-burning or smouldering fires are likely



Heat Detector

- : The XP95 heat detector monitors temperature by using a single thermistor which provides a count output proportional to the external air temperature.



Multisensor

- : The XP95 multisensor detector contains an optical smoke sensor and a thermistor temperature sensor whose outputs are combined to give the final analogue value



standalone smoke detector

- : High sensitivity - responds to all standard fires
- : Dual Ionization chamber - quick response to fast flaming fires
- : Battery powered - 9V (supplied)
- : Needs no wiring
- : Missing battery indicator
- : Low battery warning



Beacon and sounders

- : Includes a built-in-circuit loop isolator
- : DIP Switch addressable
- : Excellent lateral sound distribution
- : 92Db(a) sound output @ 1m
- : 15 selectable industry standard tone pairs and 7 volume levels (selectable at panel)
- : Group addressing facility allows multiple sounders to be operated simultaneously



Manual Call Points

- : Double terminal wire connectors for independent input and output connections
- : No glass element to break, lose or incorrectly fit when installing
- : Complete functional test with every activation
- : Pre-opened conduit entries from top, bottom and the back



Polarised Fire Bell



FIRE EXTINGUISHER



EXIT SIGNS



BATTERY



FIRE BLANKET



FIRE RESISTANT ALARM CABLE

ACCESS CONTROL AND INTERCOM



F18 Biometric Access Control

- : 1500 user capacity
- : 30,000 event log
- : Reads finger and/or cards
- : Inbuilt serial and Ethernet ports
- : Request to exit and door sensor contacts
- : Tamper proof switch



F21 : 1

- : Displays, 2.4-inch TFT LCD Colour Screen
- : Fingerprinting Capacity, 3,000
- : Card Capacity, 5000 (optional) ID or Mifare card
- : Transaction Capacity, 100,000
- : Communication, RS232/485, TCP/IP < USB-host



f22:

- : Display, 2.4-inch TFT LCD Colour Screen
- : Fingerprint Capacity, 3000
- : Card capacity, 5000 (optional) ID or Mifare card
- : Transaction Capacity, 30,000



Biometric Access Control by Zkteco:

- : Fingerprint Capacity 1000
- : ID Card Capacity 1000 (optional)
- : Record Capacity 80,000
- : Display 2.8-inch TFT Screen
- : Communication TCP/IP, USB Host
- : Optional Functions ID/Mifare
- : Software ZKTime.net 3.0



inBio460:

- : cards Holders capacity: 30,000
- : Fingerprint Capacity: 3,000
- : Log/Events Capacity: 100,000
- : Controls 4 doors



Card Readers

- : Water proof
- : Have backlit keypads
- : More than 500 users capacity



Key switches , exit buttons and maglock



KCV-A374

- : Clear image and high resolution
- : LCD OSD Menu
- : Communication between main monitor and sub units
- : Low power consumption
- : Connection upto 2 doors camera's



KC-MC30

- : Manual Camera angle adjustment
- : Weather proof
- : Door lock connection
- : Night automatic illumination



KIP-611PG

- : 11 CH Multiple interphone and doorphone
- : Single or multiple connection
- : All master intercom system
- : Paging function
- : Easy wiring and installation



Merlin 4 Energizer

- : Siren trigger times and frequency can be adjusted as required.
- : Gate chime to notify if the gate as required
- : Bypass options for the siren, strobe and gate as required
- : Siren times can be programmed to suit the different needs of the user



Druid Energizer

- : High Voltage
- : Earth wire monitors alarm when tampered with
- : Connectable to an armed response radio
- : Gate monitor input monitors the position of the gate to indicate if open
- : Battery backup system in case of power failure
- : Intelligent power saving to extend the battery life and save energy



Wizard 4 Energizer

- : Output energy at 500ohms 3.7j
- : Single zone security energizer
- : Maximum voltage setting: 800v
- : Power consumption: 12v
- : Accepts upto 4 keypads
- : Programmable outputs; 8
- : Zone expander compatible remote or board



Hammer Energizer

- : Fence monitor
- : Gate monitor
- : Strobe/siren driver
- : ON/OFF Reset keys
- : output Energy at 500ohms 5.0j
- : Remote control option
- : solar power option.



GALVANISED HIGH TENSILE WIRE FENCE



RAZOR WIRE FENCE



UNDERGATE CABLE



W INSULATOR



WARNING SIGN

ELECTRONIC ARTICLE SURVEILLANCE



DR LABEL STICKER



MINI PENCIL TAG



GROOVE PIN



DETACHER



GOLF TAG



BOTTLE TAG



DEACTIVATOR



ANTENNA



SECURITY WORLD TECHNOLOGY LTD.

Security & Safety Solution Provider

HEAD OFFICE

Industrial Area Commercial Street, Yogi Corp Business Center, 1st Flr - Rm 1B
P.O.BOX 5096-00506, NAIROBI, KENYA.

TEL: +254 728-607-000 | Mobile: +254-725-206238

Email: info@securityworldtech.com

Facebook: Security World Technology Limited

Twitter: @securityworldke, Instagram: securityworldke

Web: www.securityworldtech.com

Branches

KENYA

Nairobi CBD
Tsavo Centre,
Tsavo Road, Ground Floor,
Cell: +254 721 710 382
E-mail: info@securityworldtech.com

UGANDA

Ntinda industrial Area Plot M275
Opp, Britania Kampala
Tel: +256 777 146 635
Cell: +256 782 115 464,
E-mail: info@securityworldtech.co.ug

RWANDA

Kigali, Remera,
Kisimenti
Tel: +250 252 581 741
Cell: +254 788 382 626
E-mail: info@securityworldtech.co.rw

TANZANIA

Hifadhi Export Processing Zone Ubungo
O Morogoro Road, Dar es Salaam
Tel: +255 22 277 3391,
Cell: +255 767 607 000,
E-mail: info@securityworldtech.co.tz